

MID DETECTOR

	MID	<input type="text"/>	-	<input type="text"/>	/	<input type="text"/>	-	<input type="text"/>	/	<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>	/	<input type="text"/>	-	<input type="text"/>	
Model																			
MID electromagnetic flow meter																			
Type																			
Type 2																			2
Type 3																			3
Type 5																			5
Type 6																			6
Size																			
DIN 6 to DN 2000																			
Pressure rate																			
Process connection																			
DIN flanges																			F
ANSI flanges																			A
Threads acc. DIN 11851																			D
Tri-Clamp®																			T
Wafer																			W
Material																			
C-steel																			ST
SST 1.4301 (ANSI 304)																			V2
SST 1.4404 (ANSI 316)																			V4
Liner																			
PTFE																			PT
(DN 6-10)																			PFA
Hard rubber																			HG
Softrubber																			WG
Halar																			HA
Electrodes																			
Measure + empty pipe electrode																			ML
Measure + grounding + empty pipe electrode																			MEL
Electrode material																			
Hastelloy C																			HC
Tantalum																			TA
Platinum/gold plated																			PG
Platinum/Rhodium																			PR
Housing																			
C-steel																			St
SST 1.4301 (ANSI 304)																			V2
SST 1.4404 (ANSI 306)																			V4

Example:

MID 2 - 100 / 16 - F / St - HG - ML / HC - St

ORDER

MID AMPLIFIER

			m
--	--	--	---

Amplifier

M1000 (92-275 VAC)	M10A
M1000 (9-36 VDC)	M10D
M1000 blind version (VAC)	MB10A
M1000 blind version (VDC)	MB10D
M1000 blind version, with stainless steel housing (VAC)	MBS10A
M1000 blind version, with stainless steel housing (VDC)	MBS10D
M2000 (85-265 VAC)	M20A
M2000 (9-36 VDC)	M20D
M3000 (85-265 VAC)	M30A
M3000 (24 VDC)	M30D
M4000 (85-265 VAC)	M40A
M4000 (24 VDC)	M40D
M5000 (battery-operated/no battery pack)	M50B0
M5000 (battery-operated/1 battery pack)	M50B1
M5000 (battery-operated/2 battery packs)	M50B2
Line powered (battery back-up/100-240 VAC)	M50AB
(9-36 VDC)	M50DB

Mounted/remote/cable length

Amplifier detector mounted	M
Remote version cable length	R

Remote amplifier with cable length

Remote amplifier with 10 m cable length	10
Remote amplifier with 15 m cable length	15
Remote amplifier with 20 m cable length	20
Remote amplifier with 25 m cable length	25
Remote amplifier with 30 m cable length	30

Example:

M10A	R	15
------	---	----

 m

Medium

Temperature

Application

.....

Company

.....

Contact person

Phone

Fax

E-mail

ORDER